OPTIMISING OWN PV CONSUMPTION WITH PV ENERGY YIELD PREDICTIONS FROM MACHINE LEARNING ALGORITHMS AND WEATHER DATA

37th EU PVSEC 2020, Online Event, 7-11 September 2020, Session 6BV54

Horst Heck , Armin Schmidt, Franziska Kuonen, Sania Bacha, Eva Schüpbach, Urs Muntwyler
Bern University of Applied Sciences BFH, Burgdorf - Switzerland

Partner:

SCCER - FURIES
Shaping the FUtuRe SwIss Electrical InfraStructure

Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Innosuisse - Schweizerische Agentur für Innovationsförderung

A tool to predict PV power is created. Machine learning algorithms (MLA) are developed and fed with data recorded at six PV plants in Switzerland and weather forecasts from two Swiss providers. The prediction precision is increased by 30% when additional weather parameters are included in the MLA learning process. Own PV consumption is expected to increase with good PV predictions.

Data

- AC-power records from 6/2016 to 6/2020
- 6 Swiss PV plants (3 urban, 3 alpine)
- Weather forecast data (0/2020-6/2020) provided by MeteoSuisse and Meteoblue



6 PV plant locations (yellow: used so far; blue: future use)

Algorithm

1st step: Gaussian Process
Input: Measured AC-power at PV plants
2nd step: Neural Network
Input: - Predictions from step 1
- Basic NWP (Pictocode, GHI)
- Additional weather parameters (temperature, wind, humidity, etc.)



Results 1. Input lengths of Pictocode/GHI

(Pictocode: Abstract description of weather situation, e.g., clear sky, cloudy, etc.)

More than 1 input value increases performance



Alpine plants (red, yellow, purple) benefit more



2. Weather Parameters

Additional weather parameters tested
- Temperature
- Humidity
- Pressure
- Wind
- Timestamp (hour)





Alpine PV plants vs urban PV plants:
Temperature and humidity are more important for alpine than for urban PV plants.
Urban PV plants benefit from wind parameters.

Conclusions

- Future and past values of forecast for pictocode and GHI should be included as input.
- Further weather parameters such as temperature, wind, humidity, etc. improve the performance of the algorithm. The combination of parameters yields the best results.
- A performance increase of about 30% has been achieved so far.

Comparison of MAE for «First Try» (1 pictocode value as input) and «Optimised algorithm» (9 pict.+GHI values and additional weather param.)

Plant	First Try	Optim.	Diff.	Increase %
Burgdorf Tiergarten (Bu1)	0.0662	0.0486	0.0176	36 %
Mont Soleil (MoS)	0.0700	0.0513	0.0187	36 %
Worblenpark, Ittigen (WoP)	0.0666	0.0456	0.0210	46 %
Jungfraujoch (Jun)	0.0717	0.0535	0.0182	34 %
Birg (Bir)	0.0807	0.0573	0.0234	41 %
Burgdorf, Schlossmatt (Bu2)	0.0617	0.0472	0.0145	31 %



Test of 20 trainings per plant with optimal configuration

Acknowledgements. This research is part of the activities of the Swiss Centre for Competence in Energy Research on the Future Swiss Electrical Infrastructure (SCCER-FURIES), which is financially supported by the Swiss Innovation Agency (Innosuisse - SCCER program). We further thank Meteoblue (www.meteoblue.ch) and MeteoSuisse (www.meteosuisse.ch) for providing weather forecast data. We also gratefully acknowledge funding from Bern University of Applied Sciences BFH, Burgdorf, Switzerland.

Berner Fachhochschule

Technik und Informatik
Photovoltaik-Labor and
Institute for Optimisation and Data Analysis, IODA

Prof. Dr. Horst Heck
Jlcoweg 1 | 3400 Burgdorf | Schweiz
ioda.bfh.ch | iem.bfh.ch/photovoltaik | www.pvtest.ch
horst.heck@bfh.ch

source: https://doi.org/10.24451/arbor.13343 | downloaded: 12.10.2024